



Multiband Ku/Ka Shipboard Antenna

Specifications

Parameter	Performance	
Frequency Range	Receive: Ku-band: 10.95-12.75 GHz Ka-band: 20.2-21.2 GHz	Transmit: 13.7-14.5 GHz 30.0-31.0 GHz
Polarization: Ku-band Ka-band	Receive: H or V LHCP or RHCP	Transmit: V or H Transmit: RHCP/LHCP
Ku Polarization Alignment	up to 360 °	
Ku: Cross Polarization Ka: Axial Ratio	≥ 35 dB < 1dB	
Isolation	Ku-band TX/RX >70 dB & Ka-band TX/Rx > 90 dB	
Power Handling	200 Watts	
Sidelobe Levels	MIL-STD-188-164A	
G/T	Ku-band: 20.4 dB/K & Ka-band: 23 dB/K	

Features:

- Simultaneous Ku/Ka antenna, developed for the NANSEN Frigate upgrade program
- High power capacity
- High efficiency shaped dual reflector

Contact

3311 E. Renner Road, Suite 100
Richardson, TX 75082 USA
1.469.330.5020

multiband@comtechtel.com

About Comtech

Comtech Telecommunications Corp. (Nasdaq: CMTL) designs, develops, produces and markets innovative products, systems and services for advanced communications solutions. The Company sells products to a diverse customer base in the global commercial and government communications markets. For more information visit www.comtechtel.com.

Command & Control Technologies™

275 West Street
Annapolis, MD 21401 USA
Toll Free: 1.800.557.5869
Outside US: +1.410.263.7616
www.comtechtel.com